



## HT-PVC plate

HT-PVC板材 (象牙白)



## CPVC plate

CPVC板材 (浅灰色)



尺寸	厚度 (mm)	重量 (kg)
122cm × 244cm	3	12.5
122cm × 244cm	5	20.8
122cm × 244cm	8	33.5
122cm × 244cm	10	41.7
122cm × 244cm	12	50.0
122cm × 244cm	15	62.5
122cm × 244cm	20	83.3
122cm × 244cm	25	104.1

尺寸	厚度 (mm)	重量 (kg)
122cm × 244cm	3	12.9
122cm × 244cm	5	21.5
122cm × 244cm	8	34.8
122cm × 244cm	10	43.0
122cm × 244cm	12	51.6
122cm × 244cm	15	64.6
122cm × 244cm	20	85.8
122cm × 244cm	25	107.3

- **颜色:** 常用色、浅灰、象牙白以及其它用户要求的颜色。
- **特点:** 光洁度高、便于加工、耐腐蚀性强、电气绝缘性能可靠、寿命长、防紫外线、防静电耐高温及耐压性能高于一般同类产品。
- **适用范围:** 化工、石油、电镀、水净化处理设备、萃取箱工程、化学品槽、容器、机台设备外壳、结构体、风管、排烟系统等。
- **规格:** 1220\*2440mm / 1500\*3000mm ■ **厚度:** 3mm~25mm
- **CPVC适用温度:** -20℃~95℃ ■ **UPVC适用温度:** -10℃~55℃
- **Color:** commonly used color, light gray, ivory and other colors of user requirements.
- **Features:** high quality finish, easy processing, high corrosion resistance, electrical insulation performance, reliable, long life, anti-UV, anti-static properties of high temperature and pressure higher than similar products.
- **Application:** widely used in chemical, petroleum, electroplating, water purification equipment, extraction box engineering, chemical tank, container, machine equipment, shell, structure, duct, exhaust system and other aspects.
- **Size:** 1220 \* 2440mm / 1500 \* 3000mm ■ **Thickness:** 3mm ~ 25mm
- **CPVC suitable temperature:** -20 °C ~ 95 °C ■ **UPVC suitable temperature:** -10 °C ~ 55 °C

## 塑胶板材系列

Thermoplastic Plate Series